Dane aktualne na dzień: 13-11-2026 19:24

Link do produktu: https://winmar.pl/blackmagic-video-assist-5-3g-p-176309.html

Blackmagic Video Assist 5” 3G



Cena brutto	**1 899,00 zł**
Cena netto	**1 543,90 zł**
Dostępność	**Dostępny w sprzedaży**

Opis produktu

Blackmagic Video Assist 5 3G
Monitor i Rejestrator Video 5'' Full HD dla Profesjonalistów

Odkryj nowy wymiar kontroli i precyzji w produkcji wideo dzięki Blackmagic Video Assist 5 3G. To kompaktowe i wszechstronne urządzenie, które pozwala na monitorowanie i nagrywanie wideo w najwyższej jakości, sprawiając, że każdy kadr staje się arcydziełem.



Główne cechy:

- 5-Calowy Full HD Ekran: Jasny, precyzyjny ekran o rozdzielczości Full HD dla doskonałego monitorowania obrazu.

- Rejestracja w ProRes i DNxHD: Zapisuj materiał wideo w popularnych formatach ProRes i DNxHD, gwarantując wysoką jakość i kompatybilność z różnymi programami do postprodukcji.

- 3G-SDI i HDMI Wejścia/Wyjścia: Zapewnia pełną elastyczność łączności z różnymi urządzeniami, w tym kamerami, switcherami i innymi źródłami wideo.

- Peaking, Zebra i False Color: Zaawansowane funkcje asysty wizualnej, które ułatwiają uzyskanie idealnej ekspozycji i ostrości.

- Profesjonalne Audio Monitoring: Precyzyjne kontrolowanie dźwięku dzięki wbudowanym głośnikom i złączom słuchawkowym.

- Ultrakompaktowy Design: Lekki, przenośny i łatwy w użyciu – idealny do zastosowań w terenie i studiu.

- Zintegrowane Zasilanie Akumulatorowe: Długi czas pracy na jednym ładowaniu, eliminując konieczność częstej wymiany baterii.

- Wsparcie dla Standardów UHD i HD: Doskonała jakość obrazu zarówno dla formatów Ultra HD, jak HD.

- Bogaty Pakiet Funkcji Postprodukcji: Odczytuj, edytuj i konwertuj pliki bezpośrednio z karty SD ułatwiając cały proces postprodukcji









Blackmagic Video Assist 5 3G to niezbędne narzędzie dla każdego profesjonalisty w branży wideo, oferujące zaawansowane funkcje monitorowania i nagrywania w kompaktowej formie. Osiągnij najwyższą jakość wideo i zwiększ precyzję swojej produkcji dzięki temu innowacyjnemu monitorowi.

Specyfikacja

Łącza

SDI Video Inputs

1 x Micro BNC

SDI Video Outputs
1 x Micro BNC

SDI Rates
270Mb, 1.5G, 3G

HDMI Video Inputs
1

HDMI Video Outputs
1

Analog Audio Inputs
None, embedded audio only.
Analog Audio Outputs
1 x 3.5mm headphone jack.
Built in Speaker
Mono
Screen Dimensions
5 inch 1920 x 1080.
Screen Brightness
300nits
SDI Audio Inputs
16 channels embedded via SDI
SDI Audio Outputs
16 channels embedded via SDI
HDMI Audio Inputs
8 channels embedded via HDMI
HDMI Audio Outputs
8 channels embedded via HDMI
Remote Control
None
SD Interface
1 x UHS-I SD slot.
Storage Type
SDXC UHS-I and SDHC UHS-I SD cards.
Supports DS, HS, SDR12, SDR25, DDR50, SDR50 and SDR104 SD cards.
Computer Interface
1 x USB Type-C for webcam out, initial setup, software updates and Video Assist Utility software control.

Standardy wideo SDI

SD Video Standards
525i59.94 NTSC, 625i50 PAL
HD Video Standards
720p50, 720p59.94, 720p60
1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60

1080PsF23.98, 1080PsF24, 1080PsF25, 1080PsF29.97, 1080PsF30
1080i50, 1080i59.94, 1080i60
Standardy wideo 2K
2Kp23.98 DCI, 2Kp24 DCI, 2Kp25 DCI
2KPsF23.98 DCI, 2KPsF24 DCI, 2KPsF25 DCI
SDI Compliance
SMPTE 259M, SMPTE 292M, SMPTE 296M, SMPTE 425M
SDI Metadata Support
HD RP188
Audio Sampling
Television standard sample rate of 48 kHz and 24-bit.
Video Sampling
4:2:2 YUV
Color Precision
10-bit
Color Space
REC 601, REC 709
Multiple Rate Support
SDI and HDMI switches between 270 Mb/s, 1.5 Gb/s and 3 Gb/s.

Standardy wideo HDMI

SD Video Standards
525i59.94 NTSC, 625i50 PAL
HD Video Standards
720p50, 720p59.94, 720p60
1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60
1080i50, 1080i59.94, 1080i60
HDMI Color Precision
10-bit
Copy Protection
HDMI input is unable to capture from copy protected HDMI sources. Always confirm copyright ownership before capture or distribution of content.

Nośniki

Media
1 x UHS-I SD for HD recording.
Media Type

SDXC UHS-I and SDHC UHS-I SD cards.

Obsługiwane kodeki

ProRes 422 HQ, ProRes 422, ProRes 422 LT,
ProRes 422 Proxy, DNxHD 220x, DNxHD 145,
DNxHD 45, DNxHD 220x MXF, DNxHD 145 MXF, DNxHD 45 MXF.

Sterowanie

Recorder Control
Integrated capacitive touchscreen LCD with Blackmagic OS onscreen controls for settings and navigating menus.
External Control
SDI and HDMI start/stop, timecode run.

Oprogramowanie

Software Included
Blackmagic OS

Parametry

Scopes
Waveform, RGB Parade, Vector, Histogram.
Viewing Modes
Scopes with picture in picture or picture overlay and opacity control.

Systemy operacyjne

Mac 10.14 Mojave,
Mac 10.15 Catalina lub nowsza wersja
Windows 8.1 and 10.

Wymogi zasilania

Power Supply
1 x External 12V power supply.
Compatible with Sony NP-F style batteries.
(batteries not included)

Specyfikacje środowiskowe

Operating Temperature
0° to 40° C (32° to 104° F)
Storage Temperature
-20° to 45° C (-4° to 113° F)
Relative Humidity
0% to 90% non-condensing
