

Link do produktu: <https://winmar.pl/ptzoptics-20x-sdi-g2-szara-p-174538.html>



PTZOptics 20X-SDI-G2 - Szara

Cena brutto	9 990,00 zł
Cena netto	8 121,95 zł
Dostępność	Na zamówienie

Opis produktu

PTZOptics PT20X-SDI-GY-G2

20X Optical Zoom, 3G-SDI, HDMI, IP Network RJ45, CVBS

Broadcast & Conference Camera

The PTZOptics 20X-SDI is a 1080p camera with 20X optical zoom for capturing HD images at long distances. With support for 3G-SDI, HDMI, and IP streaming (H.264, H.265, & MJPEG), this camera is ideal for broadcasting high definition video signals for broadcast, recording, or video conferencing applications.

Key features:

- 60.7 degree wide-angle lens.
- High performance in low light scenarios with Wide Dynamic Range.
- Full 1920x1080p HD Resolutions up to 60 frames per second.
- 2D and 3D noise reduction with our latest "low noise CMOS sensor".
- RS232 & RS485 (Serial), and IP (LAN/WAN) control
- H.264, H.265, & MJPEG streaming over RJ-45 LAN port
- HDMI, 3G-SDI, & IP streaming (all 3 simultaneously)
- PoE (Power over Ethernet) or 12VDC
- RTMP & RTSP IP streaming

Specyfikacja

- **Video CMOS Sensor:** 1/2.7" CMOS, 2.12 Mega Pixels
- **Frame Rate:** 1080i 60/50/30/25 1080p 60/50/30/25 720p 60/50/30/25
- **Lens:** 20x, F4.42mm-88.5mm, F1.8-F2.8
- **Lens Zoom:** 20x (Optical Zoom)
- **Field of View:** 60.7°
- **Min Lux:** 0.5 Lux at F1.8, AGC ON
- **Shutter Speed:** 1/30s – 1/10000s
- **SNR:** ≥55dB

-
- **Vertical Flip & Mirror:** Supported
 - **Horizontal Angle of View:** 3.36° (tele) to 60.7° (wide)
 - **Vertical Angle of View:** 1.89° (tele) to 34.1°(wide)
 - **Pan Movement:** $\pm 170^\circ$

 - **Tilt Rotation:** Up: 90°, Down: 30°
 - **Presets:** 10 IR Presets (255 via Serial, or IP)

 - **Video Output Interface:** SDI, HDMI, IP Streaming, CVBS
 - **Network Interface:** RJ45
 - **Audio Interface:** Line In, 3.5mm (HDMI & IP Stream Only)
 - **Communication Interface:** RS-232, RS485
 - **Baud Rate:** 2400/4800/96000 bits
 - **Power Supply Interface:** JEITA type Power Adapter (DC IN 12V)
 - **USB 2.0 Interface:** (future use)

 - **Dimension (in.):** 5.6W x 6.5H x 6.3D (7.5H w/ Tilt Up)
 - **Dimensions (mm):** 142W x 164H x 160D (189H w/ Tilt Up)
 - **Box Dimensions:** 9"x9"x10" | 228mmx254mmx228mm
 - **Camera Weight:** 3.10 lbs. (1.41kg)
 - **Boxed Weight:** 5.4 lbs. (2.45 kg)

 - **Power Supply:** 12W (Max)
 - **Input Voltage:** 12V DC (10.8 – 13.0V DC)