Dane aktualne na dzień: 10-11-2026 10:04

Link do produktu: https://winmar.pl/teradek-bolt-6-monitor-module-750-rx-p-175966.html



Teradek Bolt 6 Monitor Module 750 RX

Cena brutto	**10 925,00 zł**
Cena netto	**8 882,11 zł**
Dostępność	**Dostępny w sprzedaży - wysyłka 1-5 dni**
Producent	**Teradek**

Opis produktu

Teradek Bolt 6 Monitor Module 750 RX

Bolt 6 RX Monitor Module to odbiornik, który w czasie rzeczywistym obsługuje sygnały wideo 4K video dzięki opatentowanej przez Teradek technologii Zero-Delay technology. Teraz dzięki użyciu nowo otwartego pasma 6GHz zapewni Ci również o wiele mniej zakłóceń. Moduł**Receiver Monitor Module** montowany jest bezpośrednio na monitorach z serii **SmallHD Smart 7**. Nadajnik zapewnia odbiór sygnału wideo color accurate, True HDR w mniej niż 0.001 sekundy. **Bolt 6 Receiver Monitor Module** montowany jest bezpośrednio w tylnej części monitorów SmallHD Cine 7, 702 Touch, oraz Indie 7. Dzięki bezpośredniej integracji produktów Teradek Bolt 6, oraz monitorów Smart mogą dzielić zasilanie oraz sygnał wideo pozwalając na zredukowanie ilości kalbi potrzebnych na planie.

Zestaw zawiera

- 1 x Bolt 6 Monitor Module 750 RX V-Mount / Gold Mount
- 5 x Antenna 2dBi Rigid V 4.9-7.3Ghz RP-SMA
- 1 x Screw Socket Head Black 1/4-20 x 3/8" length
- 2 x Screw Socket Head Low Profile Black Oxide M3 x 20mm
- 1 x Hex L key 2mm size 3-3/8" length
- 1 x Hex L key 3/16" x 2 13/16" length
- 1 x HDMI Adapter Bolt 4K RX Monitor Module

Specyfikacja

Video Outputs

- 1 x HDMI 1.4b Type-A receptacle

Sdi Ancillary Data Support

- Supports reading metadata, timecode, and start/stop flags from most camera manufacturers.

Color Sampling

- SDI: YCbCr 4:2:2, 10-bit/ HDMI: RGB 4:4:4, 8-bit

Delay Tx To Rx

- <0.001sec

Supported Resolutions

- 4Kp23.98/24/25/29.97/30
- 1080p23.98/24/25/29.97/30/50/59.94/60
- 1080psf23.98/24/25/29.97/30
- 1080i50/59.94/60
- 720p50/59.94/60
- 480p50 576p59.94/60
- 480i(NTSC)/576i(PAL)

Video Compression

- Visually Lossless

Color Correction

- None

Audio Compression

- 48kHz 24-bit PCM

Audio Output

- Embedded HDMI Audio Output (2 Channel)

Dimensions

- 122mm x 94mm x 27mm

Weight

- 292g (10.3oz)

Construction

- Milled Aluminum(Chassis) and regulation-compliant PCB

Mountability

- SmallHD 7" Monitor

Configuration Interfaces

- SmallHD Monitor UI

Mobile App

- Bolt App

Usb Interface Functionality

- SmallHD Monitor UI
- 2x 5pin Locking Connector CCU (Host)

Bluetooth

- Via SmallHD Monitor

Antennas

- 5 External 2 dBi antennas (included)

Wireless

- Non-DFS Frequencies:
- 5.190 ~ 5.230 GHz, 5.755 ~ 5.795 GHz, 5.945 ~ 6.425GHz
- DFS Frequencies:
- 5.270 ~ 5.670 GHz

Rf Channel Selection

- Auto, Manual

Encryption

- AES-256, RSA-1024 key exchange

Rf Power

- 21 dbm EIRP

Range

- Up to 750 ft, line of sight

Unicast Multicast

- Can connect one Transmitter to up to 6 Receivers

Noise Rejection

- Can coexist with WiFi and 5GHz cordless phones
- Can operate up to 6 sets in same location

Interoperability

- Can receive wireless video from all ranges of Bolt 4K XT and Bolt 4K LT transmitters (limited by shortest range device)

Power Input

- 2-Pin Circular locking Connector 6-18 VDC

Battery

- None, optional Sony/Canon dual battery plate

Nominal Power Consumption

- 6 Watts

Operating Temperature

- 0-40℃