

Dane aktualne na dzień: 26-01-2026 22:49

Link do produktu: <https://winmar.pl/teradek-serv-4k-p-175495.html>



Teradek Serv 4K

Cena brutto	15 989,00 zł
Cena netto	12 999,19 zł
Dostępność	Dostępny w sprzedaży
Producent	Teradek

Opis produktu

Teradek Serv 4K

Teradek Serv 4K is an all-in-one **production streaming solution** that unites next-gen hardware with simplified UI to easily manage and share 4K HDR image quality in real time, whether you're collaborating on set or around the world. Serv 4K allows both local and cloud-based streaming with Teradek's Vuer and Core apps as well as third-party integrations like Frame.io. Up to four live camera feeds can be streamed to multiple local devices at once, even without an internet connection. Cloud-based streaming can be shared with an unlimited number of devices via MacOS, iOS, Android, or web browsers.

This next-gen hardware includes military-grade 256-bit encryption, up to 45mbps HEVC support, 10bit 4:2:2 color, and DCI-P3 and PQ 2084 color gamuts for consistent color-accuracy from first shot through final color.

Collaborate with **Serv 4K** by providing multiple viewers with access, user-specific watermarking, and tracking history. Serv 4K is easy to set up, easy to manage, and comes with tools to keep every stakeholder in the loop, wherever they are.

In the box

- 1 x Serv 4K
- 2 x Antenna 2dBi WiFi 2.4/5.8 GHz
- 1 x PSU 2pin Conn. to 30W AC Adapter (Int) Cable - 6ft
- 1 x (Bit 118) 2pin to D-Tap Cable - 18in
- 1 x SDI - BNC to BNC Cable - 10in

Specyfikacja

Video Inputs

- 1 x SD/HD/3G/6G/12G-SDI (75 Ω BNC)
- 1 x HDMI 2.0 Type-A receptacle

Hdr Support

- Yes

Video Outputs

- 1 x SD/HD/3G/6G/12G-SDI (75 Ω BNC loop out)

Bonding

- Serv 4K App

Supported Resolutions

- 4K DCI p23.98/24/25/29.97/30/50/59.94/60 1080i 50/59.94/60
- 4K UHD p23.98/24/25/29.97/30/50/59.94/60
- 1080p 23.98/24/25/29.97/30/50/59.94/60
- 1080i 50/59.94/60
- 1080PsF 23/24/25/29/30
- 720p 50/59.94/60
- 576i
- 480i

Video Compression

- ISO MPEG-4 Part 10: Advanced Video Coding (AVC)/ITU H.264
- AVC: Baseline profile, Main profile, High profile
- SO MPEG-H Part 2: High Efficiency Video Coding (HEVC)/ITU H.265
- HEVC: Main profile

Supported Video Bitrate

- 250 Kbps to 45 Mbps

Video Format Conversion Support

- Built in video scaler and deinterlacer

Number Of Encoder Streams

- Up to one 4KDCI p60 4:2:2 10bit

Color Correction

- CDL/1024 1D LUT (supports 10-bit color)
- 33x33x33 3D LUT (supports 10-bit color)

Network Protocols

- TCP/IP, UDP, HTTP, DHCP, NTP, SSL, IGMP

Supported Video Transport Protocols

- Teradek Streaming Protocol (compatible with Teradek Apps, e.g. Live:Air, Vuer)

Remote Control

- Teradek Core

Audio Compression

- AAC-LC

Audio Input

- 3.5mm Stereo Line Level Analog or Microphone in, adjustable gain

Audio Output

-
- 3.5mm Stereo Headphone output

Dimensions

- 6.25"W x 3.6"D x 1.4"H [150 x 107 x 36mm]

Weight

- 1 lb [476g]

Construction

- Milled Aluminum

Mountability

- Can be mounted horizontally or vertically with
- 1/4" 20 mounting holes

Configuration Interfaces

- Feature-rich Web UI for configuration and control
- OLED Status Display w/Nav control buttons

Recording Storage

- SD Card: Full Size

Usb Interface Functionality

- 2x Powered USB-C host ports with 3G/4G modem support

Ethernet

- 1x 10/100/1000 BASE-T Gigabit Ethernet (RJ45)

Wireless

- WiFi: 2.4/5GHz 802.11 a/b/g/n/ac/ax MiMo

Power Input

- 2-pin circular locking connector

Nominal Power Consumption

- 18W

Auxiliary Power Input

- 6-28V DC